



# Ball/Pintle Hook

Model Number:

74115    74116    74117    74118    74119



Part Number	Description	Max. Tongue Weight (lbs)	Max. Gross Trailer Weight (lbs)	
			Ball Hitch	Pintle Hitch
74115	1-7/8" Combination Ball & Pintle	3000	6,000	16,000
74116	2" Combination Ball & Pintle	3000	10,000	16,000
74117	2-5/16" Combination Ball & Pintle	3000	14,000	16,000
74118	10 Ton Regular Pintle	4000		20,000
74119	15 Ton Regular Pintle	6000		30,000

 **This Instruction Sheet contains IMPORTANT safety information. Please read and keep for future reference.**

For assistance with this product or to order replacement parts, please contact:



**Cequent Consumer Products, Inc.**  
 29000-2 Aurora Road  
 Solon, OH 44139  
 Technical Service: (800) 234-6992  
 CequentConsumerProducts.com

Date of Purchase: \_\_\_\_\_

## **⚠️ WARNING**

**READ and FOLLOW all instructions and safety messages before using the Ball/Pintle.**

**To reduce the risk of serious injury or death to you, your passengers, and others on the road:**

**⚠️ DO NOT lubricate threads, bolt failure may occur due to over tightening.**

**⚠️ DO NOT drill or weld to this hitch.**

**⚠️ DO NOT exceed vehicle or mounting rating.**

**WARNING: Other steps and inspections are required. Consult D.O.T. regulations and American Trucking Association for complete coupling and uncoupling procedures.**

**WARNING: Be careful with the drawbar when coupling and uncoupling to avoid damaging the latch.**

**WARNING: Maintain adequate vertical (tongue) load to properly control the trailer (approximately 10%) not to exceed above rated capacities.**

**WARNING: For off-road applications, reduce the rated capacities by 25 percent.**

**THIS WARNING IS GIVEN IN COMPLIANCE WITH CALIFORNIA PROPOSITION 65**

**WARNING:** This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

## **CAUTION**

**Use only REESE supplied or approved bolt, locknuts, and washer to install.**

## Installation Instructions

Before mounting the Ball/Pintle confirm that there will be no interference from the tow vehicle and any other mounted accessories. Check for interference again after installation is complete.

1. Mounting structure must be capable of supporting the rated capacity of the pintle hook in accordance with SAE J849b.
2. Use the four 1/2" diameter grade 8 bolts and torque to 100ft. lbs.
3. For combination pintle hooks, torque ball locknut to 350ft. lbs.

## Operating Instructions

### PINTLE HOOK

1. Open pintle by removing safety pin and lifting latch.
2. Position lunette eye over the horn of the pintle and lower into place.
3. Close pintle and insert safety pin.

### HITCH BALL/PINTLE

1. Open pintle by removing safety pin and lifting latch.
2. Replace safety pin in hole to retain latch in open position.
3. Position coupler over ball and lock into place, following coupler manufactures instructions.

## Maintenance

1. Clean and inspect for proper operation every 30,000 miles or 3 months, whichever comes first.
2. Regularly lubricate latch and lock pivots with a light oil lubricant.
3. Check all mounting bolts and ball locknut for proper torque.
4. Replace ball locknut if torque falls below 70ft. lbs.

## **REESE One (1) Year Limited Warranty**

1. **Warranty.** Cequent Consumer Products, Inc. warrants to the original consumer purchaser ("You") that the Product will be free from defects in material or workmanship for one year from the date of your retail purchase. Cequent Consumer Products, Inc. makes no other warranties. If the Product does not comply with the Warranty, Cequent Consumer Products, Inc. will replace the Product without charge and within a reasonable time or, at Cequent Consumer Products, Inc. option, otherwise refund the purchase price.
2. **Limitations on the Warranty.** The Warranty does not cover the following: (a) normal wear and tear; (b) service or labor charges incurred in removing or replacing any Product; (c) the finish on the Product; (d) a Product that has been damaged through abuse, neglect, misuse or as a result of any accident or in any other manner; (e) a Product which is misapplied, overloaded, or improperly installed; and (f) a Product altered in any manner by anyone other than Cequent Consumer Products, Inc.
3. **Obligations of Purchaser.** To obtain the benefits of the Warranty, You must promptly present the defective Product and proof of purchase to Cequent Consumer Products Inc., 29000-2 Aurora Road, Solon, Ohio 44139 or any of its branches, factories, or authorized dealers listed in local directories. Any returned Product that is replaced or refunded becomes the property of Cequent Consumer Products, Inc.
4. **Legal Rights.** This Warranty gives You specific legal rights, and You also may have other rights which vary from state to state. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON ANY PRODUCT SHALL BE LIMITED TO ONE YEAR FROM THE DATE OF RETAIL PURCHASE BY YOU. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to You.
5. **Remedy Limits.** Replacement of the Product or refund in the manner provided above is Your exclusive remedy and shall constitute fulfillment of all liabilities of Cequent Consumer Products, Inc. to You whether based on contract or otherwise. Cequent Consumer Products, Inc. shall not be liable or assume responsibility for the loss of the use of any vehicle, loss of time, rental of vehicles, loss or damage to personal property, expenses such as gasoline, telephone, lodging, or towing, or any other incidental or consequential damages incurred as a result of the use or ownership of any Product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to You. Any of the above remedy limitations shall be inoperative to the extent they are not permitted by applicable state law.

The proper attachment of this product in accordance with the enclosed instructions is critical to its proper performance. Cequent Consumer Products, Inc. has no control over, or responsibility for, the attachment or the installation. Cequent Consumer Products, Inc. is NOT responsible nor will be held liable for any damage resulting from its attachment or improper use. Cequent Consumer Products, Inc. shall not be liable for any claims of any kind greater than the purchase price of the product. Warranty information available at [www.trimascorp.com/terms](http://www.trimascorp.com/terms).



**Cequent Consumer Products, Inc.**  
29000-2 Aurora Road  
Solon, OH 44139  
Technical Service: (800) 234-6992  
[CequentConsumerProducts.com](http://CequentConsumerProducts.com)